

DATA SHEET OF HYDRAULIC FLUID



GERMAN
TECHNOLOGY



ZITTA SAE ISO-VG32



DATA SHEET OF HYDRAULIC FLUID

SPECIFICATION LEVEL

AFNOR NF E 48- 603; ISO 11158

TYPICAL PROPERTIES

Density @ °15C,kg/l	ASTM D1298	0.875
Viscosity @ °100C,cSt	ASTM D445	5.4
Viscosity @ °40C, cSt	ASTM D445	32
Viscosity Index	ASTM D2270	102
Pour Point,°C	ASTM D97	- 27
Flash Point,°C	ASTM D92	227



ZITTA SAE ISO-VG46



DATA SHEET OF HYDRAULIC FLUID

SPECIFICATION LEVEL

AFNOR NF E 48- 603; ISO 11158

TYPICAL PROPERTIES

Density @ °15C,kg/l	ASTM D1298	0.8880
Viscosity @ °100C,cSt	ASTM D445	6.8
Viscosity @ °40C, cSt	ASTM D445	45.9
Viscosity Index	ASTM D2270	100
Pour Point,°C	ASTM D97	- 27
Flash Point,°C	ASTM D92	232



www.zittalubricants.de



info@zittalubricants.de

ZITTA SAE ISO-VG68



DATA SHEET OF HYDRAULIC FLUID

SPECIFICATION LEVEL

AFNOR NF E 48 - 603; ISO 11158

TYPICAL PROPERTIES

Density @ °15C,kg/l	ASTM D1298	0.884
Viscosity @ °100C,cSt	ASTM D445	8.7
Viscosity @ °40C, cSt	ASTM D445	67.8
Viscosity Index	ASTM D2270	100
Pour Point,°C	ASTM D97	- 21
Flash Point,°C	ASTM D92	240